

FIBERLOCK TECHNOLOGIES



KILLS AND PREVENTS MOLD AND MILDEW*

ACTIVE INGREDIENT:
Chlorothalonil.....0.48%
OTHER INGREDIENTS.....99.52%
TOTAL..... 100.00%

EPA Reg. No. 73884-01
EPA Est. No. 73884-MA-01

Keep Out of Reach of Children
Caution: See back panel for additional
precautionary statements

5 U.S. Gallons
Max VOC Content:200 g/l

WHITE - 8390

www.fiberlock.com

| FIRST AID | |
|---|---|
| Have the product label or MSDS with you when calling a poison control center or doctor, or going for treatment. | |
| IF IN EYES: | Hold eye open and rinse slowly and gently with water for 15-20 minutes. Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye. Call a poison control center or doctor for further treatment advice. |
| IF INHALED: | Move person to fresh air. If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably by mouth, if possible. Call a poison control center or doctor for further treatment advice. |
| IF SWALLOWED: | Do not induce vomiting unless told to do so by a poison control center or doctor. Do not give any liquid to the person. Do not give anything by mouth to an unconscious person. |
| IF ON SKIN OR CLOTHING: | Take off contaminated clothing. Rinse skin immediately with plenty of water for 15-20 minutes. Call a poison control center or doctor for treatment advice. |
| FOR MEDICAL ASSISTANCE, CALL YOUR LOCAL POISON CONTROL CENTER or 800-222-1222 | |

PRECAUTIONARY STATEMENTS HAZARDS TO HUMANS

CAUTION

Harmful if swallowed or inhaled. Avoid breathing spray mist. Avoid contact with skin, eyes, or clothing. Wash thoroughly with soap and water after handling. Remove contaminated clothing before reuse. When applying with a sprayer, applicator should wear a dust/mist filtering respirator (MSHA/NIOSH approval number prefix TC-21C) or a NIOSH approved respirator with any R, P, N, or HE filter.

PHYSICAL AND CHEMICAL HAZARDS

Do not apply this product in or on electric equipment due to the possibility of shock hazard.

CAS. No.:

7732-18-5
13463-67-7
25265-77-4

57-55-6
Not Available

CHEMICAL INGREDIENTS

Water
Titanium dioxide
2,2,4-Trimethyl-1,3-Pentenediol
Monoisobutyrate
Propylene glycol
Latex resin solids**
**contents partially unknown

MADE IN THE USA

Manufactured by:
Fiberlock Technologies, Inc.
Andover, MA 01810
(800) 342-3755
www.fiberlock.com

AfterShock is an extremely durable acrylic finish, developed to withstand moist humid conditions that provide the ideal environment for fungal growth. This easy to apply coating offers the ultimate in durability in combination with excellent fungicidal characteristics.

DIRECTIONS FOR USE

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

Check with all local, state, and federal regulations before beginning work or using this product. Fix the source of any moisture problems prior to remediation. Do not attempt to salvage damaged or structurally unsound building materials. Consult with a qualified professional to perform a thorough inspection and supply work specifications appropriate to the project.

*AfterShock is designed to kill residual mold and mildew remaining after pre-cleaning contaminated surfaces, as well as to inhibit the future growth and spread of mold and mildew on the cured film surface in residential & institutional buildings. AfterShock is recommended for use on interior wall surfaces such as plaster, wallboard, Sheetrock®, concrete, masonry block, wood, primed metal and galvanized metal. AfterShock is also recommended for use on interior wood framing, primed metal, concrete, and wallboard inside the wall cavity. Do not use for HVAC system application.

SURFACE PREPARATION: AfterShock is supplied ready to use. Stir thoroughly. Do not mix with any other coatings, solvents or colors in oil. Remove damaged materials and clean surfaces. Patch surface irregularities with an appropriate patching compound. AfterShock is self-priming over bare gypsum drywall, composition board, ceiling tile and concrete. Do not apply when air or surface temperature is below 50°F or when drying conditions are poor. Keep from freezing. Use adequate ventilation during application.

APPLICATION TOOLS: Apply AfterShock with brush, roller or airless spray equipment. If using airless spray equipment, AfterShock can be successfully applied with a .017- .019 tip setting.

COVERAGE:

Smooth Surfaces- 300-350 ft² per gallon
Porous Surfaces- 175-300 ft² per gallon
Spray- 50% of above

MOLD & MILDEW CONTROL: Remove gross filth or heavy soil. For heavily soiled areas, a pre-cleaning step is required. Apply AfterShock generously and uniformly by brush or airless spray and ensure that the surface is completely coated. Allow to air dry. Clean and inspect regularly for damage to coating film- reapply if cured coating film becomes damaged.

DRYING TIME @ 70°F 50% R.H.

To Touch - 1 Hour

CLEAN UP: Clean tools and drippings with warm soapy water before AfterShock dries.

STORAGE AND DISPOSAL

Do not contaminate water, food or feed by storage or disposal.

Pesticide Storage: Close container after each use. Keep from freezing.

Pesticide Disposal: Wastes resulting from the use of this product may be disposed of on site or at an approved waste disposal facility.

Container Disposal: Triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or incineration, or, if allowed by state and local authorities, by burning. If burned, stay out of smoke.